

Product Code 15-A143-05-08 Installation Instructions 3D File Photometry Dialux | ULD



Levels 1 Body Ø220mm

Nahtrang Design

Ceiling fixture Levels 1 Body Ø220mm LED 28 SW 2700-3000-4000K CASAMBI Black 1850lm

Technical features

Luminaire total power: 28W Real lumens: 1850 (3000K)

Real Im/W: 66

Correlated Colour Temperature (CCT): SW 2700-3000-4000K

Lens / reflector angle: HORIZONTAL 101°

Structure material: Steel Structure finish: Black Diffuser material: Glass Diffuser finish: Green

Voltage / frequency: 110-277V/50-60Hz

Dimming protocol: CASAMBI

Power Factor: NULL

Useful life: 50,000h L80B20

Warranty: 5 años

Easily recyclable luminaire











Luminotechnic features

CRI: 90

MacAdam steps: 3

Photobiological risk: RG1

	Lampholder	Quantity	Light source power (W)
Γ	LED	1	24.4W






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 15-A143-05-08 Installation Instructions 3D File Photometry Dialux | ULD




Levels 1 Body Ø220mm

Nahtrang Design

Ceiling fixture Levels 1 Body Ø220mm LED 28 SW 2700-3000-4000K CASAMBI Black 1850lm

Bluetooth range



The Bluetooth range largely depends on the obstacles and architectural features of a space, such as walls and building materials

Logistics



Net weight (kg): 2.63

Packaged weight (kg): 3.39
Packaging: 325mm x 330mm x

455mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.